



SCAFFOLDING TOWERS OF AMERICA

PD6200 SERIES

★★★★ **300lbs.** LOAD CAPACITY **TYPE IA** DUTY RATING

STYLE: Podium Ladder



COMPATIBLE
SEE PAGES 59-60



Extended guard rail
holds an arsenal of tools

4 rivets attach
top to each rail

Podium step
with toe guard

Double riveted,
slip-resistant
Traction-Tred®
steps

All steps are
knee-braced

Full set
of rear
horizontals
spaced one
per foot

Model PD6204



PD6200-4C series features
durable caster assemblies
with stainless steel springs
& heavy duty step braces

EDGE360™ bracing
system protects from
every angle

- Ideal for working at fixed heights, easier to maneuver than scaffolds or lifts
- Customize your ladder top with the Lock-In Accessory System
- EDGE360™ features Intergrated Rail Shields, Energy Diffusing Geometry, and Oversized Foot Pads
- Every rivet backed up by metal plate or washer to protect rails
- Internal aluminum spreaders on 8' and 10' models

SPECIFICATIONS

Model No.	Height (Size) to Platform	Max. Reach	Approx. Width	Approx. Spread	Approx. Cu. Ft. Per Unit	Approx. Shipping Wt. Lbs.	Model No. with Casters	Approx. Shipping Wt. Lbs.
PD6203	3'	9'	26"	37"	9.2	21.0	PD6203-4C	28.3
PD6204	4'	10'	27-1/2"	43"	11.3	26.5	PD6204-4C	33.8
PD6206	6'	12'	31"	56"	16.4	32.5	PD6206-4C	39.8
PD6208	8'	14'	34-1/2"	68"	22.3	44.5	PD6208-4C	51.8
PD6210	10'	16'	38"	80"	29.1	55.5	PD6210-4C	62.8

DIMENSIONS

Platform:	16" x 19.5"	Steps:	3" wide
Front Rails:	3-1/8" wide	Rear Rails:	1-7/8" wide
Front Flange:	1-3/16" wide	Rear Flange:	1-3/16" wide

732-805-0500

3 Smalley Avenue, Middlesex, NJ 08846
scaffoldingofamerica.com